

# intersector


## Under Mirror



9 LED, Solid Color	<b>ENT2B3(x)</b>
9 LED, Solid Color, Xylex Lens	<b>ENT2B3(x)-EU</b>
18 LED, Dual Color	<b>ENT2B3(y)</b>
18 LED, Dual Color, Xylex Lens	<b>ENT2B3(y)-EU</b>

Replace (x) or (y) in the Order Number for Standard Color Selection

(x) = 9 LED Solid Colors: A=● B=● G=● R=● W=○  
(y) = 18 LED Dual Colors: D=●○ E=●○ F=●○ H=●○ J=●● K=●● L=●● M=●● N=●● P=●●



No other light offers 180 degree output - specially designed reflector amplifies and throws the light at the perfect angle to increase visibility at intersections and offer side warning illumination.

### Features

- The first light of its kind to offer critical intersection warning and side warning
- Design of light is based upon problem solving research - 30% of all emergency vehicle crashes are likely to occur at dangerous intersections
- Unique under mirror mount simplifies installation - labor saving light is much easier to install than traditional front mirror skull mounts - no mirrors to work behind or around
- Light can be surface mounted to any flat area on any type of vehicle - elevate your safety and visibility by mounting to the headache rack or body of the vehicle wherever additional lighting is needed
- Features cruise mode for steady burn if desired
- Light includes three mounting wedges (0, 5, 10 and 15 degrees) and foam gasket
- Light has separate control functionality and is sync compatible with nFORCE® products
- Dual light allows either color to be set to flash or steady-burn
- Steady-burn white can be specified as a means of providing additional side/alley lighting
- The flasher has been integrated into the light to provide easier installation

1.800.338.7337



**Curved Surface Adaptor and Installation Bracket** *Refer to page 55*

### Technical Specifications

<b>INPUT VOLTAGE</b>	10-16 Vdc
<b>CURRENT DRAW</b>	9 LED Single Color, < 1.25 Amps; 18 LED Dual Color, < 1.25 Amps
<b>LIGHT SYNC</b>	24 single lightheads
<b>FLASH PATTERNS</b>	Solid, 30 color patterns; Dual 12 solid or 14 dual color patterns
<b>OPERATING TEMPERATURE</b>	-40° C to +65° C / -40° F to +149° F
<b>DIMENSIONS</b>	<b>Length:</b> 2.9" (7.4 cm) <b>Height:</b> 1.9" (4.8 cm) H <b>Depth:</b> 2.9" (7.4 cm)
<b>MOUNTING</b>	Under mirror or surface mount
<b>CERTIFICATIONS</b>	SAE J845 Class 1 WS3-1 (100) certified
<b>WARRANTY</b>	Five-year



# intersector

## accessories **Curved Surface Adaptor and Brackets**

Lights are sold separately.

### **Under Mirror Curved Surface Adaptors** (sold in pairs)

- a. Universal
  - Chevrolet Caprice, 2011+
  - Dodge Charger, 2011+
  - Dodge Durango, 2013-2016
  - Ford Explorer, 2013-2016
  - Ford Sedan, 2013+

- PNT1CRV01**
- PNT1CRV02**
- PNT1CRV03**
- PNT1CRV06**
- PNT1CRV05**
- PNT1CRV04**



### **Under Mirror Installation Bracket**

- a. Bracket and screws included

**PNT1WRRT**



### **Single Surface Mount Brackets**

- a. Chevrolet Tahoe
- b. Deck/Grille mount

**#PNT3DGBB-TH**  
**#PNT3DGBB**

