XF Flush Mount



Compact, flush-mount emergency light to fit seamlessly into any vehicle



FEATURES

- · Single and dual color models available
- Syncs with other Sync2 products
- bluePRINT[®] compatible

SPECIFICATIONS

Voltage	12-24 Vdc
Current Draw	0.81A @ 12 Vdc / 0.41A @ 24 Vdc (varies by flash pattern)
Flash Patterns	20
LED Color Capabilities	Single ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● ● </th
Operating Temperature	-30°C to +65°C
Dimensions	1.6" W x 1.51" H x 1.54" D
Mount	Flush mount
Certifications	SAE J595, ECE R65, ECE R10, CA Title 13, CISPR25 For complete certification details, please visit the installation guide for each product.
IP Rating	IP67
Warranty	Five years

· Low profile flush mount design

2 (select models)

· Advanced LED output - SAE Class 1 and ECE R65 Class



Scan to order or learn more

CONTACT

Toll free 800.338.7337 Direct 616.896.7100 **soundoffsignal.com** PO Box 206 Hudsonville, MI 49426 customerservice@soundoffsignal.com V0523