

DIGI 10, LTE 700, Ch 21-48 (Color box)

Art. Number 105460



TRIAX UHF LTE 700 Aerials

Disruption free installation from rooftop to outlet.

- Interference protection from LTE 700 & 800 signals
- Quick and easy installation with semi-assembled aerials
- Mechanical filtering for higher gain
- Reliable high-quality aerials secures end-consumer satisfaction
- Corrosion and weather proof dipole housing
- Designed to receive DTT signals in the 470...694 MHz range
- Access to reliable, expert support from TRIAX

Technical Specifications

ORDER INFORMATION

EAN Number 5702661054600

FREQUENCY RANGE

Band UHF
 Channels 21...48
 Frequency range UHF | MHz 470...694 MHz
 LTE protection @ 700Mhz

GAIN

Gain | dBi max 13 dBi
 Gain @ 474 MHz (Ch. 21) | dBi 9.5 dBi

LOSS

Rejection @ 788 MHz (Ch. 60) | dB 7.6 dB

ELECTRICAL

Front to back ratio - horizontal | dB 15 dB

MECHANICAL



Technical Specifications

Elements	10
Windload @42 m/s N	22 N
Beamwidth horizontal °	±30 °
Bracketry	Mast bracket - rear
Main material	Aluminium
Packing QTY	10
Product Length mm	1085 mm
Product Width mm	480 mm
Packaging Height m	0.075 m
Packaging Width m	0.210 m
Packaging Depth m	1.100 m
Packaging Volume m3	0.017 m3
Net Weight kg	0.730 kg
Tara Weight kg	0.400 kg
Total Weight kg	1.130 kg