



KOKWI 3 IEC coax plug, angled, female

Art. Number 153111



KOKWI 3 IEC coax plug, angled, female. These IEC coax plugs are designed with a view of very easy mounting without compromising technically correct installation. Frequency range 0-2400 MHz. Stain relief for any cable 4,5-7,2 mm. Packing: Multi colour box contains 50 pcs. packed individually in polybags. Assembly guide is printed on each polybag.

Technical Specifications

ORDER INFORMATION

EAN Number 5702661531118

SHIELDING

Shielding @ 30-1000 MHz | dB > 75 dB

Shielding @ 1000-2000 MHz | dB > 55 dB

CHARACTERISTICS

Cable type KOKA 6DS / F6 TSV / 110 UV / 125H

FREQUENCY RANGE

Frequency range | MHz 0...2400 MHz

RETURN LOSS

Return Loss | dB ≥ 18 (@862MHz) - ≥ 6 (@2400MHz) dB

ELECTRICAL

Impedance | Ω 75 Ω

OPERATIONAL

Screening Efficiency EN50117 (Class A)

Temperature - operating | $^{\circ}\text{C}$ -25...55 $^{\circ}\text{C}$

CONNECTORS

Adaptable Cable Diameters - Inner Conductor | mm max 1,13 mm

Adaptable Cable Diameters - Outer Conductor | mm max 5,6 mm

Adaptable Cable Diameters- Jacket | mm 4,5...7,2 mm



Technical Specifications

MECHANICAL

Dimensions carton (H x D x W) mm	50' pack 173x206x90 mm
Packing QTY	1/50
Product Height mm	40.5 mm
Product Length mm	34 mm
Product Width mm	17.3 mm
Packaging Height m	0.020 m
Packaging Width m	0.045 m
Packaging Depth m	0.055 m
Packaging Volume m ³	0.000 m ³
Net Weight kg	0.019 kg
Tara Weight kg	0.002 kg
Total Weight kg	0.021 kg
Remarks	Packed in single polybag, 50 pcs in colour box.