

YSHIELD® GK5 | Primer concentrate | 1 liter

High quality primer supplied as concentrate, makes 5 liters of primer. TÜV-SÜD certified.



YSHIELD® GK5

YSHIELD GmbH & Co. KG
94099 Ruhstorf, Germany
www.yshield.com
info@yshield.de

High quality primer supplied as concentrate, makes 5 liters of primer. For priming of solid old coats of paint, brittle, chalky and absorbent substrates. Consolidating, adhesion promoting, good penetration, regulates the absorbency. Also recommended on our graphite shielding paints HSFxx, if **problematic (mineralic) coatings** should be applied.

Processing

Mix the concentrate (1 liter) **with 4 liters of water. Gives 5 liters of primer.** If you use tap-water, process within 48 hours. For application use a first-class paint roller. Do not work at temperatures below 5°C/41°F. The consumption depends on the character and absorbency of the underground. Typical interior productivity 37.5 m², typical exterior productivity 25 m².

Ingredients

Pure-acrylic binder, additives, preservative (BIT, INN, MIT).

TÜV-SÜD certification

We have our shielding paints monitored by TÜV-SÜD. The whole production process including quality control, emission behaviour and economical use of preserving agents is subject to monitoring. **Please find the certificate above at the downloads.**